
ASTRUP

ASTRUP 70 B2C MARS MARS CRB 430 700-827 BPI CL1 MR P1










- Color: MARSALA (RAL 3011)
- Internal anodized finishing aluminum gear unit cover: BRASS
- Housing: Co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: Stainless steel 316L painted MARSALA (RAL 3011)
- External metal parts in 316L stainless steel and screws in A4 stainless steel
- Structure: MARSALA (RAL 3011) powder-coated aluminium with anti-corrosion treatment
- Gaskets: Gaskets moulded in EPDM




Light specifications and controlling

- High-efficiency removable LED modules (IRC>80, 3 SDCM)
- Luminous flux: 700 lm
- Colour temperature: 2700 K
- Dimming: Built-in dimming button



Installation and maintenance

- Structure dimensions: 600 x 350 x 162 mm
- Provided with 4m 5G1,5 cable with tinned copper meshwork under transparent tubing with a european plug IP44
- Easily removable LED modules and driver



Characteristics

• Warranty: 5 years

• 50 000 h L80/B10 at 25°C

• Operating temperature: -20°C to +30°C

• Protection: IP68

• Resistance to IK shocks: IK10

Electrical class: Class I

• Power supply: 220-240 V 50/60 Hz

• Power consumption: 13 W

Photobiological hazard: Group 0

• Fire resistance: 650 °C

• Weight: 5 kg